

LC Fiber Optic Patch Cord



Features

- *High return loss
- *Low insertion loss
- *Telcordia style boots
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 ℃ to +85 ℃	-40 ℃ to +85 ℃

SC Fiber Optic Patch Cord



Features

- *High return loss
- *Low insertion loss
- *Telcordia style boots
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 ℃ to +85 ℃	-40 ℃ to +85 ℃

ST Fiber Optic Patch Cord



Features

- *High return loss
- *Low insertion loss
- *Telcordia style boots
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 ℃ to +85 ℃	-40 ℃ to +85 ℃

FC Fiber Optic Patch Cord



Features

- *High return loss
- *Low insertion loss
- *Telcordia style boots
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 ℃ to +85 ℃	-40 ℃ to +85 ℃

MTRJ Fiber Optic Patch Cord

MU Fiber Optic Patch Cord



Features

- *High return loss
- *Low insertion loss
- *Telcordia style boots
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

Features

- *High return loss
- *Low insertion loss
- *Telcordia style boots
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

SPECIFICATIONS		
	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 °C to +85 °C	-40 °C to +85 °C

SPECIFICATIONS		
	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 °C to +85 °C	-40 °C to +85 °C

E2000 Fiber Optic Patch Cord



Features

- *High return loss
- *Low insertion loss
- *High bit-rate protocols
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 °C to +85 °C	-40 °C to +85 °C

DIN Fiber Optic Patch Cord



Features

- *High return loss
- *Low insertion loss
- *Compatible with DIN 47256
- *Compliance with TIA/IEA,IEC,Rohs

Applications

- *CATV,Metro,LANs
- *Active device termination
- *Telecommunication networks
- *Industrial,medical & military

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	plug and unplug 1000times	
Operating Temperature	-40 °C to +85 °C	-40 °C to +85 °C

SMA Fiber Optic Patch Cord



Features

- *Metal ferrules, Simplex only and Multimode only.
- *High return loss
- *Low insertion loss
- *SMA patch cord with high reliability and stability

Applications

- *Telecommunication
- *Testing equipment
- *Long-haul telecommunication
- *LAN system
- *CATV systems

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB	
Repeatability	≤0.1dB	
Tensile strength	>10kg	
Durability	plug and unplug 1000times	
Operating Temperature	-40 ℃ to +85 ℃	-40 ℃ to +85 ℃

Bundle fan out Patch Cord



Features

- Meet IEC, Telcordia-GR-326 and JIS performance requirement;
- High return loss and low insertion Loss.
- Good reliability and stability
- Polishing type: PC, UPC, and APC
- Various interfaces: FC, SC, ST...
- Core of cable: 4, 6, 8, 12...

Applications

- *Telecommunication
- *LAN & WAN system
- *CATV systems
- *FTTP

SPECIFICATIONS

	Single Mode	Multimode
Insertion Loss	<0.20dB	<0.25dB
Return Loss	≥50 dB	
Repeatability	≤0.1dB	
Interchangeability	≤0.2dB	
Durability	≤0.2dB typical change, 1000 matings	
Operating Temperature	-40 ℃ to +85 ℃	-40 ℃ to +85 ℃